



All-In-One Convenience!

All-in-one convenience is what the DC-D Drum filter cart is all about. The simple practicality of this cart allows the operator to dispense and filter oil out of a 55 gallon drum on wheels. A magnetic kickstand adds stability and ensures the drum will not tip over. The drum filter cart has ability to filter oil viscosities up to 600cSt (ISO VG 680) at 100°F within ambient temperature ranges of -15°F to 150°F.

Typical Applications

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- · Dispensing new oil

Performance:

For filtering mineral and synthetic based oils (hydraulic oils, gear oils and turbine oils) with a maximum operating viscosity range of ISO VG 680 (3000ssu/648cSt) at 100°F within ambient temperature ranges of -15°F to 150°F.

Standard Features:

Materials:

- · Frame: Carbon steel; flat free tires
- · Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- · Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

 Slide bar differential indicators trigger at 50 psid when elements need to be changed

Pump Relief:

Opens at 150psi

Weight:

Approx. 145lbs (will vary depending on options)

Dimensions:

Approx. 23"L x 21"W x 59"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	ß4(c)=2000	14/12/9 - 13/11/8
P1065	ß7(c)=2000	18/16/13 - 15/13/10
P1063	ß10(c)=1000	19/17/14 - 18/16/13
P1064	ß25(c)=2000	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".

Components:

Item Number	Description	Qty.
1	Heavy Duty Drum Cart	1
2	Motor	1
3	Gear Pump	1
4	Filter Head	2
5	Filter Element	2
6	Filter Indicator	2
7	Sample Port	2
8	Switch On/Off	1
9	Cord Reel	1
10	Kick Stand	1



